

## alpha intro home theater system



**The 6-piece Alpha Intro Home Theater System offers ultra-compact, high performance versatility for home theater, music and multimedia applications. Included in one compact box are four Intro LR satellite speakers, an Intro CLR center channel and the SubZero *i* powered subwoofer. Perfectly matched and magnetically shielded the Front, Center and Surround satellites guarantee seamless, lifelike surround sound imaging. This system has the efficiency and power handling that's absolutely necessary to deliver the full emotional impact of both music and dynamic film soundtracks.**

The original Alpha was one of the most famous products in audio history, establishing a benchmark for high performance and value in compact speakers. The Alpha Intro Home Theater System continues in its footsteps, utilizing newly developed drivers and modular construction to provide improved performance, especially with the new aluminum-dome tweeter that delivers

silky, extended, and detailed high-frequency response. It goes almost without saying that for home theater and serious music listening alike, effective deep-bass reproduction is a must. PSB's ultra-compact SubZero *i* meets the challenge with a specialized long-throw driver, an efficient, bass-extending enclosure, and a highly dynamic, low-frequency-optimized on-board amplifier. The SubZero *i* produces as much as 260 watts, for unconstrained deep-bass peaks.

Audiophile-grade terminals, proprietary-designed drivers and subwoofer circuitry, plus a host of built-in mounting options for installation flexibility are just a few of the "details" you don't expect to find on other "value" speakers.

Their elegant blonde woodgrained finish blends unobtrusively into any decor providing the perfect solution to your home theater needs.

# alpha intro home theater system

	<b>Alpha Intro LR</b> Bookshelf/Surround	<b>Alpha Intro CLR</b> Center/Bookshelf/Surround	<b>Alpha SubZero i</b> Powered Subwoofer
<b>Frequency Range Response</b> On Axis @ 0°±3dB Off Axis @ 30°±3dB LF Cutoff -10dB	(Anechoic Chamber) <b>100-21,000Hz</b> 100-10,000Hz <b>90Hz</b>	<b>90-21,000Hz</b> 90-10,000Hz <b>80Hz</b>	<b>36-150Hz</b>  <b>32Hz</b>
<b>Sensitivity</b> Anechoic Chamber Typical Listening Room	(1W (2.83V) @ 1m, IEC-filtered Pink Noise, C-weighted) 85dB <b>87dB</b>	86dB <b>88dB</b>	
<b>Impedance</b> Nominal Minimum	<b>6 Ohms</b> 4 Ohms	<b>8 Ohms</b> 6 Ohms	<b>22kOhms</b> 1kOhm 4 Ohms (Woofer Only)
<b>Input Power Recommended</b> Program	(RMS, Clipping <10% Time) <b>15-80 Watts</b> 60 Watts	<b>15-80 Watts</b> 60 Watts	(Internal Amplifier) <b>100 Watts Continuous</b> 130W Dynamic, 260W Peak
<b>Acoustic Design</b> Tweeter (Nominal)  Woofer (Nominal)  Crossover  Internal Volume Design Type	<b>3/4" (19mm)</b> Aluminum Dome with Ferrofluid <b>3 1/2" (90mm)</b> Polypropylene Cone Rubber Surround <b>3,000Hz, B3</b>  <b>0.07 cu ft (2.0 liter)</b> <b>Acoustic Suspension</b> Sealed <b>Video Shielded</b>	<b>3/4" (19mm)</b> Aluminum Dome with Ferrofluid <b>2 x 3 1/2" (90mm)</b> Polypropylene Cone Rubber Surround <b>3,000Hz, B3</b>  <b>0.10 cu ft (2.8 liter)</b> <b>Acoustic Suspension</b> Sealed <b>Video Shielded</b>	<b>8" (200mm)</b> Polypropylene Cone Rubber Surround <b>Variable 50-150Hz, LR4</b> Low Pass Filter <b>0.68 cu ft (19.3 liter)</b> <b>Bass Reflex</b> 1" x 8" Front Duct <b>Video Shielded</b> Radiused In/Externally
<b>Size (W x H x D)</b>	<b>4 1/4 x 6 3/4 x 6 1/4"</b> 108 x 171 x 159mm	<b>9 3/4 x 4 1/4 x 6 1/4"</b> 248 x 108 x 159mm	<b>9 5/8 x 13 1/4 x 14 1/2"</b> 244 x 337 x 368mm Feet add 1" (25mm)
<b>Weight</b> Net Shipping	<b>3.3 lb (1.5kg)/each</b> 7.6 lb (3.5kg)/pair	<b>4.8 lb (2.2kg)/each</b> 5.6 lb (2.6kg)/each	<b>23.0 lb (10.5kg)/each</b> 27.0 lb (12.3kg)/each
<b>Finish</b>	<b>Blonde</b> Woodgrained	<b>Blonde</b> Woodgrained	<b>Blonde</b> Woodgrained
<b>Features</b>	<b>5-way Gold-plated Binding Posts</b> Keyhole Slot 1/4-20 Threaded Brass Insert Aluminum Grille Clear Rubber Bumpers	<b>5-way Gold-plated Binding Posts</b> Hor/Vert Keyhole Slots 1/4-20 Threaded Brass Insert Aluminum Grille Clear Rubber Bumpers	<b>Front Mounted Volume, Crossover,</b> Phase, Bypass, On, Standby/Off Low Level/LFE Input, High Level Input Gold-plated RCAs 5-way Binding Posts Feet

PSB Speakers reserves the right to change specifications or features without notice.

© 2002 PSB Speakers, a division of Lenbrook Industries Limited.

PSB is a registered trademark of Lenbrook Industries Limited. All rights reserved. No part of this publication may be reproduced, stored or transmitted in any form whatsoever without the written permission of PSB Speakers.